

## SAFETY DATA SHEET

Revision Date: 08/12/2011  
Print Date: 2/9/2012  
MSDS Number: R0065154  
Version: 3.9

VALVOLINE™ AW 68 HYDRAULIC OIL  
VV044

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland  
P.O. Box 2219  
Columbus, OH 43216

Regulatory Information Number  
Telephone

1-800-325-3751  
614-790-3333  
Emergency telephone number  
1-800-ASHLAND (1-800-  
2745263)

Product name VALVOLINE™ AW 68 HYDRAULIC OIL  
Product code VV044

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance: liquid

CAUTION! PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS.

#### Potential Health Effects

##### Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

##### Eye contact

Unlikely to cause eye irritation or injury.

##### Skin contact

May cause mild skin irritation. Symptoms may include redness and burning of skin. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

## SAFETY DATA SHEET

Revision Date: 08/12/2011  
Print Date: 2/9/2012  
MSDS Number: R0065154  
Version: 3.9

VALVOLINE™ AW 68 HYDRAULIC OIL  
VV044

### Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

### Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

### Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions)

### Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

### Target Organs

No data

### Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

### Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No. / Trade Secret No.	Concentration
HEAVY PARAFFINIC DISTILLATE	64742-54-7	<=100%

## SAFETY DATA SHEET

VALVOLINE™ AW 68 HYDRAULIC OIL  
VV044

Revision Date: 08/12/2011

Print Date: 2/9/2012

MSDS Number: R0065154

Version: 3.9

### 4. FIRST AID MEASURES

#### Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

#### Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

#### Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

#### Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

#### Notes to physician

**Hazards:** Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of longterm sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

**Treatment:** No information available.

### 5. FIRE-FIGHTING MEASURES

## SAFETY DATA SHEET

Revision Date: 08/12/2011  
Print Date: 2/9/2012  
MSDS Number: R0065154  
Version: 3.9

VALVOLINE™ AW 68 HYDRAULIC OIL  
VV044

### Suitable extinguishing media

Dry chemical, Carbon dioxide (CO2), Water spray

Hazardous combustion products carbon dioxide and  
carbon monoxide, Hydrocarbons Precautions for  
**fire-fighting**

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

**NFPA Flammable and Combustible Liquids Classification**  
Combustible Liquid Class IIIB

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

### Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

### Methods for cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

### Other information

Comply with all applicable federal, state, and local regulations.

## 7. HANDLING AND STORAGE

## SAFETY DATA SHEET

VALVOLINE™ AW 68 HYDRAULIC OIL  
VV044

Revision Date: 08/12/2011

Print Date: 2/9/2012

MSDS Number: R0065154

Version: 3.9

### Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. **Storage**

Store in a cool, dry, ventilated area.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

Contains no substances with occupational exposure limit values.

### General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

### Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

### Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

### Skin and body protection

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Wear resistant gloves (consult your safety equipment supplier).

## SAFETY DATA SHEET

Revision Date: 08/12/2011

Print Date: 2/9/2012

MSDS Number: R0065154

Version: 3.9

VALVOLINE™ AW 68 HYDRAULIC OIL  
VV044

### Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by airpurifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an airpurifying respirator may not provide adequate protection.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Boiling point/boiling range	(>)424.9 °F / 218.3 °C @ 760.00 mmHg
Flash point	> 390 °F / > 199 °C Cleveland open cup
Evaporation rate	(>)1 Ethyl Ether
Lower explosion limit/Upper explosion limit	1 %(V) / 6 %(V)
Vapour pressure	0.013 hPa @ 70.00 °F / 21.11 °C Calculated Vapor Pressure
Relative vapour density	(>)1 AIR=1
Density	0.8708 g/cm <sup>3</sup> @ 60.01 °F / 15.56 °C
	7.27 lb/gal @ 60.1 °F / 15.6 °C
Viscosity, kinematic	65.75 mm <sup>2</sup> /s

### 10. STABILITY AND REACTIVITY

#### Stability

Stable.

#### Conditions to avoid

None known.

#### Incompatible products

Strong oxidizing agents

Hazardous decomposition products carbon dioxide and carbon monoxide, Hydrocarbons

#### Hazardous reactions

## SAFETY DATA SHEET

VALVOLINE™ AW 68 HYDRAULIC OIL  
VV044

Revision Date: 08/12/2011

Print Date: 2/9/2012

MSDS Number: R0065154

Version: 3.9

Product will not undergo hazardous polymerization.

### 11. TOXICOLOGICAL INFORMATION Acute oral toxicity

Acute oral toxicity - Product : no data available

Acute oral toxicity - Components

HEAVY PARAFFINIC DISTILLATE : LD 50: > 15 g/kg Species: Rat

Acute inhalation toxicity

Acute inhalation toxicity - Product : no data available

Acute dermal toxicity

Acute dermal toxicity - Product : no data available

Acute dermal toxicity - Components

HEAVY PARAFFINIC DISTILLATE : LD 50: > 5 g/kg Species: Rabbit

Acute toxicity (other routes of administration)

Acute toxicity (other routes of administration) : no data available

### 12. ECOLOGICAL INFORMATION

Biodegradability

Biodegradability - Product : no data available

Bioaccumulation

Bioaccumulation - Product : no data available

Ecotoxicity effects

Toxicity to fish

Toxicity to fish - Product : no data available

## SAFETY DATA SHEET

Revision Date: 08/12/2011  
Print Date: 2/9/2012  
MSDS Number: R0065154  
Version: 3.9

VALVOLINE™ AW 68 HYDRAULIC OIL  
VV044

### Toxicity to daphnia and other aquatic invertebrates.

Toxicity to daphnia and other aquatic invertebrates.  
- Product : no data available

### Toxicity to algae

Toxicity to algae -  
Product : no data available

### Toxicity to bacteria

Toxicity to bacteria -  
Product : no data available

## 13. DISPOSAL CONSIDERATIONS

### Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

## 14. TRANSPORT INFORMATION

### REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

#### U.S. DOT - ROAD

Not dangerous goods

#### U.S. DOT - RAIL

Not dangerous goods

#### U.S. DOT - INLAND WATERWAYS

Not dangerous goods

#### TRANSPORT CANADA - ROAD



## SAFETY DATA SHEET

VALVOLINE™ AW 68 HYDRAULIC OIL  
VV044

Revision Date: 08/12/2011  
Print Date: 2/9/2012  
MSDS Number: R0065154  
Version: 3.9

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

## SAFETY DATA SHEET

Revision Date: 08/12/2011  
Print Date:  
MSDS Number: R0065154  
Version

VALVOLINE™ AW 68 HYDRAULIC OIL  
VV044

Page:

2/9/2012

: 3.9

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

### SARA Hazard Classification SARA 311/312 Classification

No SARA Hazards

### SARA 313 Component(s)

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### New Jersey RTK Label Information

HEAVY PARAFFINIC DISTILLATE

64742-54-7

### Pennsylvania RTK Label Information

HEAVY PARAFFINIC DISTILLATE

64742-54-7

### Notification status

US. Toxic Substances Control Act

y (positive listing)

Canada. Canadian Environmental Protection Act (CEPA).

y (positive listing)

Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)

Australia. Industrial Chemical (Notification and Assessment)

y (positive listing)

Act

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand

n (Negative listing)

Japan. Kashin-Hou Law List

y (positive listing)

Korea. Toxic Chemical Control Law (TCCL) List

y (positive listing)

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act

y (positive listing)

China. Inventory of Existing Chemical Substances

y (positive listing)

# ASHLAND

11

## SAFETY DATA SHEET

Revision Date: 08/12/2011  
Print Date:  
MSDS Number: R0065154  
Version

VALVOLINE™ AW 68 HYDRAULIC OIL  
VV044

	HMIS	NFPA
Health	1	1
Flammability	1	1

/ 11

Page:

2/9/2012

: 3.9

	HMIS	NFPA
Physical hazards	0	
Instability		
Specific Hazard		0
16. OTHER INFORMATION	--	--

The information accumulated herein is believed to be accurate but is not warranted to be whether

originating with the company or not. Recipients are advised to confirm in advance of need that the

# ASHLAND.

## SAFETY DATA SHEET

Revision Date: 08/12/2011  
Print Date:  
MSDS Number: R0065154  
Version

VALVOLINE™ AW 68 HYDRAULIC OIL  
VV044

information is current, applicable, and suitable to their circumstances. This MSDS has been prepared

by Ashland's Environmental Health and Safety Department (1-800-325-3751). / 11