

**SAFETY DATA SHEET**

Revision Date: 12/13/2011
Print Date: 2/9/2012
MSDS Number: R0272510
Version: 1.15

Valvoline™ DRIVE TRAIN SAE 30W
TRANSMISSION FLUID
VV323

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland
P.O. Box 2219
Columbus, OH 43216

Regulatory Information Number
Telephone

1-800-325-3751
614-790-3333
Emergency telephone number
1-800-ASHLAND (1-800-
2745263)

Product name Valvoline™ DRIVE TRAIN SAE 30W TRANSMISSION FLUID
Product code VV323

2. HAZARDS IDENTIFICATIONEmergency Overview

Appearance: liquid, amber

CAUTION! MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN AND RESPIRATORY TRACT IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE DERMATITIS AND BURNS. MAY BE HARMFUL IF SWALLOWED.

Potential Health Effects**Exposure routes**

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin contact

Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 2/9/2012

MSDS Number: R0272510

Version: 1.15

Valvoline™ DRIVE TRAIN SAE 30W
TRANSMISSION FLUID

Ingestion

VV323

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: acne, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

CAS-No. / Trade Secret No. Concentration

SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 2/9/2012

MSDS Number: R0272510

Version: 1.15

Valvoline™ DRIVE TRAIN SAE 30W TRANSMISSION FLUID

HEAVY PARAFFINIC DISTILLATE	64742-54-7	>=80-<90%
CATALYTIC DE WAXED HEAVY PARAFFINIC	64742-70-7	>=5-<10%
VV323		
OIL (PETROLEUM)		
MINERAL OIL		>=1.5-<5%
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	>=1.5-<5%
CALCIUM LONG-CHAIN ALKYLPHENATE SULFIDE		>=1.5-<5%
ZINC DIALKYL DITHIOPHOSPHATE	68649-42-3	>=1-<1.5%
4. FIRST AID MEASURES		

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of longterm sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms

SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 2/9/2012

MSDS Number: R0272510

Version: 1.0

Valvoline™ DRIVE TRAIN SAE 30W TRANSMISSION FLUID

are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, VV323

irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIREFIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon dioxide (CO₂), Water spray

Hazardous combustion products carbon dioxide and carbon monoxide,
Hydrocarbons, sulfur oxides

Precautions for fire-fighting

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 2/9/2012

MSDS Number: R0272510

Version: 1.15

Valvoline™ DRIVE TRAIN SAE 30W
TRANSMISSION FLUID
Methods for cleaning up
VV323

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Other information

Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Store in a cool, dry, ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

CATALYTIC DE WAXED H (PETROLEUM)	NAVY PARAFFINIC OIL	64742-70-7	
NIOSH	Recommended exposure limit (REL):	5 mg/m3	Mist.
NIOSH	Short term exposure limit	10 mg/m3	Mist.
OSHA Z1	Permissible exposure limit	5 mg/m3	Mist.
ACGIH	time weighted average	5 mg/m3	Inhalable fraction.
MINERAL OIL			
NIOSH	Recommended exposure limit (REL):	5 mg/m3	Mist.
NIOSH	Short term exposure limit	10 mg/m3	Mist.
OSHA Z1	Permissible exposure limit	5 mg/m3	Mist.
ACGIH	time weighted average	5 mg/m3	Mist.
ACGIH	Short term exposure limit	10 mg/m3	Mist.

SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 2/9/2012

MSDS Number: R0272510

Version: 1.15

Valvoline™ DRIVE TRAIN SAE 30W TRANSMISSION FLUID

ACGIH NIC	time weighted average	0.2 mg/m3	Inhalable fraction.
HYDROTREATED LIGHT PARAFFINIC DISTILLATE			
NIOSH	Recommended exposure limit (REL):	5 mg/m3	Mist.
VV323			
NIOSH	Short term exposure limit	10 mg/m3	Mist.
OSHA Z1	Permissible exposure limit	5 mg/m3	Mist.
ACGIH	time weighted average	5 mg/m3	Inhalable fraction.

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Wear resistant gloves (consult your safety equipment supplier).

Discard gloves that show tears, pinholes, or signs of wear.

Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by airpurifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any

SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 2/9/2012

MSDS Number: R0272510

Version: 1.15

Valvoline™ DRIVE TRAIN SAE 30W TRANSMISSION FLUID

potential for uncontrolled release, exposure levels are not known or any other circumstances where an airpurifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

VV323

Physical state	liquid
Colour	amber
Odour	hydrocarbon-like
Flash point	> 390 °F / > 199 °C Cleveland open cup
Lower explosion limit/Upper explosion limit	1 %(V) / 6 %(V) Calculated Explosive Limit
Vapour pressure	1.333 hPa @ 68 °F / 20 °C Calculated Vapor Pressure
Density	0.900 g/cm ³ @ 60.00 °F / 15.56 °C

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid

excessive heat

Incompatible products

Strong oxidizing agents

Hazardous decomposition products carbon dioxide and carbon monoxide, Hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.

SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 2/9/2012

MSDS Number: R0272510

Version: 1.15

Valvoline™ DRIVE TRAIN SAE 30W
TRANSMISSION FLUID

11. TOXICOLOGICAL INFORMATION Acute oral toxicity

Acute oral toxicity - : no data available
Product

VV323

Acute oral toxicity - Components

HEAVY PARAFFINIC : LD 50: > 15 g/kg Species: Rat
DISTILLATE

CATALYTIC DE : LD 50: > 2,000 mg/kg Species: Rat Remarks: Information
WAXED HEAVY given is based on data obtained from similar substances.
PARAFFINIC OIL
(PETROLEUM)

ZINC DIALKYL : LD 50: 2,000 - 5,000 mg/kg Species: Rat
DITHIOPHOSPHATE

Acute inhalation toxicity

Acute inhalation toxicity - : no data available
Product

Acute dermal toxicity

Acute dermal toxicity -
Product : no data available

Acute dermal toxicity - Components

HEAVY PARAFFINIC : LD 50: > 5 g/kg Species: Rabbit
DISTILLATE

CATALYTIC DE : LD 50: > 2,000 mg/kg Species: Rabbit Remarks:
WAXED HEAVY Information given is based on data obtained from similar
PARAFFINIC OIL substances.
(PETROLEUM)

ZINC DIALKYL : LD 50: > 2,000 mg/kg Species: Rabbit
DITHIOPHOSPHATE

Acute toxicity (other routes of administration)

Acute toxicity (other routes : no data available
of administration)

12. ECOLOGICAL INFORMATION

SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 2/9/2012

MSDS Number: R0272510

Version: 1.15

Valvoline™ DRIVE TRAIN SAE 30W
TRANSMISSION FLUID
VV323

Biodegradability

Biodegradability - Product : no data available

Bioaccumulation

Bioaccumulation - Product : no data available

Ecotoxicity effects

Toxicity to fish

Toxicity to fish - Product : no data available

Toxicity to daphnia and other aquatic invertebrates.

Toxicity to daphnia and : no data available

other aquatic invertebrates.

- Product

Toxicity to algae

Toxicity to algae - : no data available

Product

Toxicity to bacteria

Toxicity to bacteria -

Product : no data available

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 2/9/2012

MSDS Number: R0272516

Version: 1.1

Valvoline™ DRIVE TRAIN SAE 30W
TRANSMISSION FLUID
VV323

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods



SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 2/9/2012

MSDS Number: R0272510

Version: 1.15

Valvoline™ DRIVE TRAIN SAE 30W
TRANSMISSION FLUID

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID
VV323

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

SARA Hazard Classification

SARA 311/312 Classification

Acute Health Hazard

SARA 313 Component(s)

ZINC DIALKYL DITHIOPHOSPHATE 1.29 %

New Jersey RTK Label Information

HEAVY PARAFFINIC DISTILLATE	64742-54-7
CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM)	64742-70-7
MINERAL OIL	
LUBRICANT ADDITIVE	
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8
ZINC DIALKYL DITHIOPHOSPHATE	68649-42-3

SAFETY DATA SHEET

Revision Date: 12/13/2011

Print Date: 2/9/2012

MSDS Number: R027251

Version: 1.15

Valvoline™ DRIVE TRAIN SAE 30W
TRANSMISSION FLUID

Pennsylvania RTK Label Information

HEAVY PARAFFINIC DISTILLATE	64742-54-7
CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM)	64742-70-7
MINERAL OIL	
LUBRICANT ADDITIVE	
VV323	
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8

Notification status

US. Toxic Substances Control Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	y (positive listing)
Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	n (Negative listing)
Japan. Kashin-Hou Law List	y (positive listing)
Korea. Toxic Chemical Control Law (TCCL) List	y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	y (positive listing)
China. Inventory of Existing Chemical Substances	y (positive listing)

	HMIS	NFPA
Health	1	1
Flammability	1	1
Physical hazards	0	
Instability		0
Specific Hazard	--	--

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).